

➔ Specifications

Parameter	Specification	
Center Wavelength (λ_c)	ITU Grid	
Channel Spacing	200 GHz	
Channel Pass Band	$\lambda_c \pm 0.25$ nm	
Insertion Loss (Express Channel)	0.5 dB	
Insertion Loss (Add/Drop Channel)	0.8 dB	
Pass Band Ripple	0.5 dB	
Adjacent Channel Isolation	30 dB	
Non-Adjacent Channel Isolation	40 dB	
Express Channel Isolation	12 dB	
Directivity	50 dB	
Return Loss	45 dB	
PDL	0.1 dB	
PMD	0.1 ps	
Maximum Power	300 mW	
Operating Temperature	0° C ~ + 65° C	
Storage Temperature	- 40° C ~ + 85° C	
Package Dimensions	Bare fiber (B)	5.5 mm () x 35 mm (L)
	900 μ m loose tube (L)	5.5 mm () x 40 mm (L)

Note1: All values specified are without connectors.

Note2: Higher performance specifications are available upon request.

Note3: Fiber type Corning SMF-28e.

Note4: Over operating temperature, all SOP.

➔ Ordering Information

A	D	-		-	2	-		-		-		-		-		-	
		Type		Channel Spacing		1st ITU Channel #		Fiber Length		Pigtail Style		Connector					
		A: Add D: Drop		2: 200 GHz		e.g. 23: 1558.98 nm		A: 1 meter B: 1.5 meter S: Special		(=Package style) B: bare fiber L: 900 μ m loose tube		0: None 7: LC/UPC 1: FC/PC 8: LC/SPC 2: FC/APC 9: Special 3: SC/PC A: FC/UPC 4: SC/APC B: SC/UPC 5: FC/SPC C: ST 6: SC/SPC					