

➔ Specifications (50/50)

Parameter	Premium	A Grade
Operating Wavelength Range	1310 & 1550 nm ± 40 nm	
Insertion Loss (Max)	≤ 3.6 dB	≤ 3.8 dB
Uniformity (Typical)	≤ 0.7 dB	≤ 1.0 dB
Return Loss	≥ 55 dB (1x2) ≥ 65dB (2x2)	
PDL	≤ 0.15 dB	≤ 0.20 dB
TDL	≤ 0.2dB	
Operating & Storage Temperature	- 40° C ~ + 85° C	
Package Dimensions	Light Duty (B)	3.0mm (Φ) x 55.0mm (L)
	Medium Duty (L)	3.0mm (Φ) x 60.0mm (L)
	Heavy Duty (K, R)	100.0mm x 12.0mm x 8.0mm

➔ Tap Coupler

Coupling Ratio	Max Insertion Loss	
	Premium	A Grade
40/60	4.7/ 2.7 dB	5.0/2.9 dB
30/70	6.0/1.9 dB	6.4/2.2 dB
20/80	7.9/1.2 dB	8.5/1.4 dB
10/90	11.3/0.6 dB	12.7/0.8 dB
5/95	15.0/0.4 dB	16.0/0.5 dB
1/99	23.5/0.3 dB	24.0/0.4 dB

Note1: All values specified are without connectors.

Note2: Higher performance specifications are available upon request.

Note3: Fiber Type – Corning SMF-28e.

➔ Tree Couplers

*Port #	Max IL		Uniformity	
	Premium	A Grade	Premium	A Grade
1 x 4	7.2 dB	7.6 dB	1.3 dB	1.8 dB
1 x 8	11.0 dB	11.3 dB	2.0 dB	2.4 dB
1 x 16	14.4 dB	15.2 dB	2.7 dB	3.2 dB

*Other port numbers upon request.

➔ Ordering Information

D	W	C	Grade	Coupling Ratio	Fiber Length	Pigtail Style	Connector
12: 1 x 2	22: 2 x 2	14: 1 x 4	P: Premium	XY % : XY %	1: 1 meter	(=Package style)	0: None
18: 1 x 8	116: 1 x 16	A: A Grade	EVEN: Even split	2: 2 meter	B: bare fiber	1: FC/PC	7: LC/UPC
				S: Special	L: 900 μm loose tube	8: LC/SPC	2: FC/APC
					K: 2mm cable	9: Special	3: SC/PC
					R: 3mm cable	A: FC/UPC	4: SC/APC
						B: SC/UPC	5: FC/SPC
						C: ST	6: SC/SPC